

Technical datasheet

AirLoc 707


 Art. no.
3.07052.70

Universally applied, long-term stability.

Ideal load p

10.0 daN/cm²

Article information	
Type	707
Name	AirLoc 707
Art. no.	3.07052.70
Color	yellow green



Technical Data		Dimensions	
Profile	double	Length L [mm]	1000
Hardness [° Shore A]	70 - 75	Width B [mm]	500
Load p from [daN/cm ²]	5.0	Pad thickness unloaded [mm]	5
Load p to [daN/cm ²]	20.0	Pad thickness tolerance web	DIN 7715/T5/P3
Ideal load p [daN/cm ²]	10.0	Range of application	
Vertical natural frequency at ideal load f _{0v} [Hz]	63.0	Temperature range from [°C]	-15
Horizontal natural frequency at ideal load f _{0h} [Hz]	16.5	Temperature range to [°C]	100
Tolerance natural frequency +/- [Hz]	10%		
Vertical damping ratio D at ideal load [%]	27.5		
Tolerance +/-	10%		
Coefficient of friction on concrete with fine mortar	0.85		
Coefficient of friction tolerance +/-	0.1		
Weight [kg]	2.2		

Diagram vertical natural frequency




 Tolerance natural frequency vertical f_{0v} [Hz] 10%
 +/-

Diagram deflection



Tolerance Deflection s +/- 10%

Standard pad dimensions

Article no.	Length [mm]	Width [mm]
3.07052.70	1000	500
3.07052.71	500	500

3.07052.72	500	250
3.07052.76	250	250
3.07052.80	200	200
3.07052.85	125	125
3.07052.86	100	100
Other dimensions in all shapes available from stock upon request.		