

Technical datasheet

Jacmounts pat.
PRG 170 /405

Art. no.
1.16170.43

Extremely stable. Best suited for light machines and systems for which there is permanently defined ground contact.


Max. load
2000 daN

Article information	
Type	PRG 170 /405
Name	Jacmounts pat.
Art. no.	1.16170.43
Color	RAL 7001 silver grey
Other colors upon request.	
Surface treatment	painted

Type illustration



Dimensioned sketch



Technical Data		Dimensions	
Max. load [daN]	2000	Height H [mm]	25
Weight [kg]	1.7	Height H _{min} [mm] M16	52.5
Temperature range from [°C]	-20	Height H _{min} [mm] M20	63.5
Temperature range to [°C]	80	Height H _{min} [mm] M24	74.5
Pad equipment		Diameter D [mm]	170
Bottom pad type	405		
Pad thickness unloaded [mm]	5		
Coefficient of friction on concrete with fine mortar	0.9		
Hardness [° Shore A]	40 - 45		
Bottom pad area A ₁ [cm ²]	201		

Suitable studs, special studs, leveling screws, leveling sockets



Special studs G2

M16, M20, M24

[more](#)

Useful remarks

The body of the element and the special levelling stud are, once installed, connected with each other, forming one single unit. The special levelling stud is exchangeable at any time by means of a patented connection.

Remark extent of supply

Special studs need to be ordered separately.

Mounting sketch

