

Technical datasheet

Jacmounts pat.
PRG 230 /905

Art. no.
1.16230.73

For applications with high static load. Excellent leveling stability and high overall stability. Very economical.


Max. load
6000 daN

Article information	
Type	PRG 230 /905
Name	Jacmounts pat.
Art. no.	1.16230.73
Color	RAL 7001 silver grey
Other colors upon request.	
Surface treatment	painted



Technical Data		Dimensions	
Max. load [daN]	6000	Height H [mm]	27
Weight [kg]	4.186	Height H _{min} [mm] M16	53
Temperature range from [°C]	-20	Height H _{min} [mm] M20	63.5
Temperature range to [°C]	80	Height H _{min} [mm] M24	74.5
		Diameter D [mm]	230

Pad equipment	
Bottom pad type	905
Pad thickness unloaded [mm]	5
Coefficient of friction on concrete with fine mortar	0.8
Hardness [° Shore A]	90 - 95
Bottom pad area A ₁ [cm ²]	380

Suitable studs, special studs, leveling screws, leveling sockets		
	Special studs G2	M16, M20, M24 more

Useful remarks
The body of the element and the special levelling stud are, once installed, connected with each other, forming one single unit. The special levelling stud is exchangeable at any time by means of a patented connection.

Remark extent of supply
Special studs need to be ordered separately.

