

# **Compact Wedgmount<sup>®</sup> Precision Levelers Type 500-QFixx**

#### Features and benefits

- Compact precision leveler for maximum design flexibility
- Bolt-on and bolt-through versions available to fit all attachment requirements
- Available as socket version for inaccesible machine feet (mineral cast machine bed)
- Centered bolt-on thread or bolt-through hole provides ideal loading for longer life
- Fast and precise levelling mechanism, for easy, safe installation
- Low leveling torque required up to maximum load capacity for easy height adjustment
- Enclosed adjustable mechanism for long term reliability
- Ruggedly designed spherical seat for uneven floors or rough machine feet
- Offers highly efficient vibration isolation performance in combination with our well-known AirLoc Isolation Pads

Modern machine design becomes more efficient with every new machine generation. Area of machine support is reduced on these new models. Therefore, the design requirements of the machine support increases daily. Typical mounting systems cannot fulfill all of these requirements.

Due to the reduction of supports in modern machine design, we have to deal with increased load requirements as well as high reliability of our leveling mounts.

AirLoc has responded to these challenges by providing the new Compact Wedgmount ® Precision Leveler, type 500-QFixx. Availability of different versions provide maximum design flexibility for a highly efficient and economic machine support design. When combined with our AirLoc Isolation Pads, the result is reduced dynamic loads on the machine structure along with providing vibration isolation performance.

Fast and precise leveling based on low adjustment torque makes machine installation easy and reliable. The centrally mounted attachment bolt ensure that the unit will remain securely clamped even when the machine is lifted off the floor for relocation. These features make the new Compact Wedgmount® Precision Leveler, type 500-QFixx an ideal tool for safe, easy and reliable machine installation and reinstallation.

## Ideally suited for the following applications:

- Milling- and Grinding machines
- Lathes
- Boring mills
- Injection molding machines
- Graphic machines
- Transfer lines
- Textile industrial machines





# **Compact Wedgmount® Precision Levelers** Type 500-QFixx features:

Ask for our new AirLoc catalogue free of charge!

Jet black RAL 9005

Color

- Compact Wedgmount® Precision Levelers where space is limited to install machine mounts
- Bolt-on and bolt-through versions are available as standard configurations
- 515-QFixx also available for subsequent anchoring version (KaBloc)
- Enclosed adjustable mechanism for maximum life
- Provides for fast and precise leveling
- Easy installation with low leveling torque required

- Rugged spherical seat version as standard for extreme torsional strength, even on uneven floors or rough machine feet
- Provides excellent vibration isolation in combination with our well-known AirLoc Isolation Pads



bolt-on	Article No.	Load daN	H mm	L mm	B mm	Levelling mm	Torque Nm
505.1-VRKC/716 505.1-VRKC/902 505.1-VRKC/915	1.36505.56 1.36505.59 1.36505.65	2500 6000 6000	78 65 78	130	105	+/- 3	40
515.1-VRKC/716 515.1-VRKC/902 515.1-VRKC/915	1.36515.56 1.36515.59 1.36515.65	4400 15000 15000	84 71 84	160	140	+/- 5	73
bolt-through							





515.1-VRKC/915	1.36515.65	15000	84					
bolt-through								
505.2-VRKC/716	1.37505.56	2500	78					
505.2-VRKC/902	1.37505.59	6000	65	130	105	+/- 3	40	
505.2-VRKC/915	1.37505.65	6000	78					
515.2-VRKC/716	1.37515.56	4400	84					
515.2-VRKC/902	1.37515.59	15000	71	160	140	+/- 5	73	
515.2-VRKC/915	1.37515.65	15000	84					





rigid clamp							
505-KSKC	1.47505	6000	63	130	105	+/- 3	40
515–KSKC	1.47515	15000	69	160	140	+/- 5	73






socket 505.6-VRKC/902 505.6-VRKC/915	1.53505-6.59 1.53505-6.65	6000 6000	65 78	130	105	+/- 3	40
515.6-VRKC/902 515.6-VRKC/915	1.53515-6.59 1.53515-6.65	15000 15000	71 84	160	140	+/- 5	73






## Mounting system KaBloc

- Only for 515-QFixx
- Load up to 15000 daN
- Levelling +/- 5 mm
- max. levelling torque 73 Nm
- Subsequent anchoring if required





## AirLoc Schrepfer AG

Industriestrasse 2, CH-8618 Oetwil am See Telephone +41 44 929 77 00, Fax +41 44 929 7710 www.airloc-schrepfer.com, info@airloc-schrepfer.com

### **Worldwide Distributors**

Please visit us in the Internet at www.airloc-schrepfer.com for details about our worldwide distributors.

All information and specifications are true and correct to the best of our knowledge; they do not represent an assurance of properties and do not release users from examination on their own, also with reference to the trademark rights of third parties. Technical revisions are subject to change without prior notice.